

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/108451 A2**

- (51) International Patent Classification<sup>7</sup>: **B60J**
- (21) International Application Number:  
PCT/IB2004/001897
- (22) International Filing Date: 10 June 2004 (10.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0313364.2 10 June 2003 (10.06.2003) GB  
0313942.5 16 June 2003 (16.06.2003) GB
- (71) Applicant (for all designated States except US): **GDX NORTH AMERICA INC.** [US/US]; 615 South DuPont Highway, Dover, DE 19901 (US).
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): **PLUM, Achim** [DE/DE]; Immeinhush 60, 41748 Viersen (DE). **PLOT-TNIK, Reimund** [DE/DE]; Wilhelm Reimes Strasse 4, 41334 Nettetal (DE).
- (74) Agent: **FOSTER, Mark, Charles**; Mathisen & Macara, The Coach House, 6-8 Swakeleys Road, Ickenham, Uxbridge UB10 8BZ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SEALING STRIP FOR A CLOSURE MEMBER



(57) Abstract: A car door comprises an outer part 1 and an inner part 3 which are coupled together by a fixing screw 21 and retainer 23. A sealing strip 7 is fitted over a terminal portion 15 of the inner door part 3 by means of adhesive tape 17. The fixing screw 21 is fitted by distorting or compressing the tubular portion 9 of the seal which brings aperture 31 into alignment with the aperture 22 through which the screw 21 is to pass. When the screw 21 has been fitted into the aperture 22, the tubular part 9 of the seal 7 is released and resiles. The fixing screw 21 serves to provide an additional means for locating the seal 7 and secures the inner door part 3 to the outer door part 1. A concealing lip 25 extending integrally from the tubular part 9 of the seal 7 conceals from view the point where the outer door part 1 and the inner door part 3 are joined together to improve the visual appearance of the door and to reduce or prevent dirt or moisture entering the space between the outer and inner door parts 1 and 3.

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/108451 A3**

(51) International Patent Classification<sup>7</sup>: **B60J 10/08**

(21) International Application Number:  
PCT/IB2004/001897

(22) International Filing Date: 10 June 2004 (10.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0313364.2 10 June 2003 (10.06.2003) GB  
0313942.5 16 June 2003 (16.06.2003) GB

(71) Applicant (for all designated States except US): **GDX NORTH AMERICA INC.** [US/US]; 615 South DuPont Highway, Dover, DE 19901 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PLUM, Achim** [DE/DE]; Immenbush 60, 41748 Viersen (DE). **PLOT-TNIK, Reimund** [DE/DE]; Wilhelm Reimes Strasse 4, 41334 Nettetal (DE).

(74) Agent: **FOSTER, Mark, Charles**; Mathisen & Macara, The Coach House, 6-8 Swakeleys Road, Ickenham, Uxbridge UB10 8BZ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: SEALING STRIP FOR A CLOSURE MEMBER



(57) Abstract: A car door comprises an outer part 1 and an inner part 3 which are coupled together by a fixing screw 21 and retainer 23. A sealing strip 7 is fitted over a terminal portion 15 of the inner door part 3 by means of adhesive tape 17. The fixing screw 21 is fitted by distorting or compressing the tubular portion 9 of the seal which brings aperture 31 into alignment with the aperture 22 through which the screw 21 is to pass. When the screw 21 has been fitted into the aperture 22, the tubular part 9 of the seal 7 is released and resiles. The fixing screw 21 serves to provide an additional means for locating the seal 7 and secures the inner door part 3 to the outer door part 1. A concealing lip 25 extending integrally from the tubular part 9 of the seal 7 conceals from view the point where the outer door part 1 and the inner door part 3 are joined together to improve the visual appearance of the door and to reduce or prevent dirt or moisture entering the space between the outer and inner door parts 1 and 3.



**(88) Date of publication of the international search report:**  
20 January 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*